

Model No. 2-Pole cage motor 23RN 160M 15kW D400V 50Hz IM2021-FF300

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	15	20	27,5	2935	48,8	N/A	89,3	0,89	6,21	1,94	2,62
690	Y				15,9								

Motor type	23RN160M02
Enclosure	IP23 Free circulation
Frame Material	Cast iron
Frame size	160M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	15 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	69 K
Temperature rise surface	28 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6310/C3
Lubrication method	15gr/6700hrs
Type of grease	0

Phase resistance at 20°C	0,4904 Ohm
Country of origin	CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	194%	614%	139%	262%	6,68 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP23
Mounting type	IM2021-FF300
Cooling method	IC01
Motor weight - approx.	132 kg
Gross weight - approx.	136 kg

Vibration level **according IEC60034-14**

Direction of rotation **cw / ccw**


PTC 150°C

No

No

No

Schematic presentation of torque-speed curve



P000012713



Driving efficiency and sustainability

