

Model No. 4-Pole cage motor 23RN 315L 315kW D400V 50Hz IM2021-FF740

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	315	425	535	1480	2032,6	IE2	95,8	0,89	6,51	1,79	2,32
690	Y				309								
460	D	60	390	522,8	589	1776	2097,1	< IE1	94,4	0,88	6,45	1,67	2,16

Motor type	23RN315LX04
Enclosure	IP23 Free circulation
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	315 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	79 K
Temperature rise surface	28 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	45gr/4000hrs
Type of grease	0

Phase resistance at 20°C	0,0079 Ohm
Country of origin	CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	179%	650%	132%	232%	125 A
@ D 460V 60Hz	167%	645%	123%	216%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP23
Mounting type	IM2021-FF740
Cooling method	IC01
Motor weight - approx.	1360 kg
Gross weight - approx.	1400 kg
Motor inertia	5,1200 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	83 dB(A)

Direction of rotation	cw /ccw
	PTC 150°C
	No
	No
	No

Schematic presentation of torque-speed curve



P000012772
P000064364



Driving efficiency and sustainability

