

Model No. 2-Pole cage motor 23RN 315S 160kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	160	214,5	265	2965	515,3	IE3	95,6	0,91	7,80	1,60	2,10
690	Y				153								

Motor type	23RN315S02E3
Enclosure	IP23 Free circulation
Frame Material	Cast iron
Frame size	315S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	160 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Rotor type	Cage motor
Bearing type	6317/C3
Lubrication method	30gr/2500hrs
Type of grease	0

Degree of protection	IP23
Mounting type	IM1001
Cooling method	IC01
Motor weight - approx.	1000 kg
Gross weight - approx.	1030 kg
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C
	No
	No
	No

Country of origin CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	160%			210%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000061657



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

