

Model No. 4-Pole cage motor 23RN 315X 400kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	400	540	691	1480	2581,1	IE2	95,8	0,88	6,22	1,60	2,55
690	Y				398								
460	D	60	460	616,6	741	1780	2468,0	< IE1	92,9	0,84	5,76	1,60	2,55

Motor type	23RN315XLB04
Enclosure	IP23 Free circulation
Frame Material	Cast iron
Frame size	315X
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	400 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	76 K
Temperature rise surface	59 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	45gr/4000hrs
Type of grease	0

Phase resistance at 20°C	0,0090 Ohm
Country of origin	CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	160%	616%	121%	255%	163 A
@ D 460V 60Hz	160%	574%		255%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30


This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP23
Mounting type	IM1001
Cooling method	IC01
Motor weight - approx.	1500 kg
Gross weight - approx.	1550 kg
Motor inertia	6,2100 kgm ²

Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	83 dB(A)

Direction of rotation	cw /ccw
	PTC 150°C
	No
	No
	No

Schematic presentation of torque-speed curve



P000012788
P000013640



Driving efficiency and sustainability

