

Model No. 4-Pole cage motor 23RN 355L 710kW D400V 50Hz IM1001

| U<br>(V) | Δ/Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|-------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D           | 50        | 710       | 951,7     | 1230     | 1485       | 4566,0    | N/A         | 95,5                               | 0,87                            | 5,26                                   | 1,58                                   | 2,42                                   |
| 690      | Y           |           |           |           | 711      |            |           |             |                                    |                                 |                                        |                                        |                                        |
|          |             |           |           |           |          |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                |                       |
|----------------|-----------------------|
| Motor type     | 23RN355Lx04           |
| Enclosure      | IP23 Free circulation |
| Frame Material | Cast iron             |
| Frame size     | 355L                  |
| Duty           | S1                    |
| Voltage        | 400 V                 |
| Frequency      | 50 Hz                 |
| Power output   | 710 kW                |

|                               |                  |
|-------------------------------|------------------|
| Insulation class              | F                |
| Ambient temperature           | -20 till 40 °C   |
| Temperature rise              | temp.rise acc. H |
| Temperature rise winding      | 80 K             |
| Temperature rise surface      |                  |
| Altitude above sea level      | 1000 mtr         |
| Hazardous area classification | Safe area        |

|                    |              |
|--------------------|--------------|
| Rotor type         | Cage motor   |
| Bearing type       | 6322/C3      |
| Lubrication method | 60gr/4000hrs |
| Type of grease     | 0            |

|                   |    |
|-------------------|----|
| Country of origin | CN |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 158%                              | 526%                           | 115%                         | 242%                           | 330 A                     |
|               |                                   |                                |                              |                                |                           |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                          |
|------------------------|--------------------------|
| Degree of protection   | IP23                     |
| Mounting type          | IM1001                   |
| Cooling method         | IC01                     |
| Motor weight - approx. | 2130 kg                  |
| Gross weight - approx. | 2190 kg                  |
| Motor inertia          | 15,3900 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14    |

|                       |           |
|-----------------------|-----------|
| Direction of rotation | cw /ccw   |
|                       | PTC 150°C |
|                       | No        |
|                       | No        |
|                       | No        |

Schematic presentation of torque-speed curve



P000015354



Driving efficiency and sustainability

