

**Model No.** 2-Pole cage motor 5RN 100L 4,6kW D230V 50Hz IM3641-FT165

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 4,6       | 6,166     | 16,9     | 2880       | 15,3      | IE1         | 84,4 84,4 82,4                     | 0,81 0,75 0,63                  | 7,97                                   | 3,73                                   | 4,32                                   |
| 400      | Y             |           |           |           | 9,75     |            |           |             |                                    |                                 |                                        |                                        |                                        |
|          |               |           |           |           |          |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 5RN100L02V                   |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 100L                         |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 4,6 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise exceeds class H    |
| Temperature rise winding      | 87 K                         |
| Temperature rise surface      | 32 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3641-FT165            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 31 kg                   |
| Gross weight - approx.             | 32 kg                   |
| Motor inertia                      | 0,0044 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 0 dB(A)                 |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6206-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,9100 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque<br>[% nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 230V 50Hz | 373%                              | 792%                           | 341%                         | 432%                           | 8,6 A                     |

### NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.



P000000412



Driving efficiency and sustainability

