

**Model No.** 6-Pole cage motor 5RN 180L 15kW D400V 50Hz IM2021-FF300

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |       |       | PF at __load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|-------|-------|--------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
|          |               |           |           |           |          |            |           |             | FL               | 3/4FL | 1/2FL | FL           | 3/4FL | 1/2FL |                                        |                                        |                                        |
| 400      | D             | 50        | 15        | 20        | 29,6     | 965        | 148,4     | IE1         | 88,8             | 89,5  | 90,1  | 0,82         | 0,78  | 0,70  | 5,58                                   | 2,34                                   | 2,51                                   |
| 690      | Y             |           |           |           | 17,1     |            |           |             |                  |       |       |              |       |       |                                        |                                        |                                        |
| 460      | D             | 60        | 18        | 24,13     | 29,6     | 1165       | 147,6     | N/A         | 90,3             | 91,5  | 91,0  | 0,84         | 0,79  | 0,71  | 5,77                                   | 2,25                                   | 2,42                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 5RN180L06A6                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 180L                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 15 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. F             |
| Temperature rise winding      | 77 K                         |
| Temperature rise surface      | 38 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM2021-FF300            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 155 kg                  |
| Gross weight - approx.             | 160 kg                  |
| Motor inertia                      | 0,1750 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 0 dB(A)                 |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6310-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,9450 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque<br>[% nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 234%                              | 557%                           | 207%                         | 251%                           | 12,6 A                    |
| @ D 460V 60Hz | 225%                              | 574%                           | 163%                         | 242%                           | 10,3 A                    |

### NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.



P000004202  
P000004211



Driving efficiency and sustainability

