

Model No. 2-Pole cage motor 5RN 250M 75kW D400V 50Hz IM2021-FF500

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	75	100	130	2975	240,8	IE2	95,2 94,0	0,89 0,87	7,97	2,33	3,10
690	Y				75								
460	D	60	84	112,6	125	3575	224,4	IE2	94,9 94,2	0,89 0,87	8,01	2,53	3,14

Motor type	5RN250M02E28
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	250M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	75 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	74 K
Temperature rise surface	41 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6215/C3
Lubrication method	23gr/3700hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0598 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	233%	776%	208%	310%	127 A
@ D 460V 60Hz	253%	798%	210%	314%	31,6 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2021-FF500
Cooling method	IC411
Motor weight - approx.	440 kg
Gross weight - approx.	450 kg
Motor inertia	0,5700 kgm ²
Vibration level	according IEC60034-14

Direction of rotation cw / ccw

Schematic presentation of torque-speed curve



P000012283
P000012296



Driving efficiency and sustainability

