

Model No. 2-Pole cage motor 5RN 280M 90kW D400V 50Hz IM2021-FF500

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	90	120	157	2975	288,9	IE2	94,3 94,0	0,88 0,85	7,53	2,31	3,10
690	Y				90,6								
460	D	60	101	135,4	151	3574	269,9	IE2	94,3 94,2	0,88 0,87	7,63	2,40	3,05

Motor type	5RN280M02E23
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	280M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	90 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	80 K
Temperature rise surface	35 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6217/C3
Lubrication method	37gr/2500hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0314 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	231%	751%	160%	310%	48 A
@ D 460V 60Hz	240%	768%	160%	305%	42,4 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2021-FF500
Cooling method	IC411
Motor weight - approx.	560 kg
Gross weight - approx.	580 kg

Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	74 dB(A)

Direction of rotation	cw / ccw
-----------------------	----------

Schematic presentation of torque-speed curve



P000011610
P000011611



Driving efficiency and sustainability

