

Model No. 6-Pole cage motor 5RN 315L 110kW D400V 50Hz IM3011-FF600

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	110	150	196	989	1062,2	IE2	95,3	94,4		0,85	0,82		7,91	2,88	2,88
690	Y				113												
460	D	60	132	175	204	1189	1060,2	IE2	95,5	95,2		0,85	0,82		7,68	2,57	2,70

Motor type	5RN315L06E26
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	110 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	54 K
Temperature rise surface	43 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0408 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	288%	790%	208%	288%	
@ D 460V 60Hz	257%	764%	208%	270%	61,4 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF600
Cooling method	IC411
Motor weight - approx.	900 kg
Gross weight - approx.	930 kg
Motor inertia	4,0200 kgm ²
Vibration level	according IEC60034-14

Direction of rotation cw / ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000012200

P000012273



Driving efficiency and sustainability

