

Model No. 2-Pole cage motor 5RN 315S 110kW D400V 50Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	110	150	187	2982	352,3	IE2	95,1	94,2		0,89	0,88		7,63	2,21	3,00
690	Y				108												
460	D	60	123	164,9	183	3581	328,0	IE2	94,7	94,3		0,90	0,87		7,55	2,30	3,00

Motor type	5RN315S02E20
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	110 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	71 K
Temperature rise surface	26 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6316/C3
Lubrication method	30gr/3000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0225 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	221%	764%	165%	300%	50,7 A
@ D 460V 60Hz	230%	748%	165%	300%	46,3 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	700 kg
Gross weight - approx.	720 kg
Motor inertia	1,3000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	75 dB(A)

Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000011612

P000011613



Driving efficiency and sustainability

