

Model No. 4-Pole cage motor 5RN 63M 0,25kW D230V 50Hz IM3641-FT100

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	0,25	1/3	1,43	1385	1,7	IE2	68,5	0,64	3,70	2,90	2,90
400	Y				0,82								
265	D	60	0,29	0,389	1,4	1705	1,6	IE2	70,0	0,64	4,20	2,90	3,00
460	Y				0,81								

Motor type	5RN63M04E26
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	63M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	0,25 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	43 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM3641-FT100
Cooling method	IC411
Motor weight - approx.	06 kg
Gross weight - approx.	06 kg

Vibration level according IEC60034-14

Direction of rotation cw / ccw

Rotor type	Cage motor
Bearing type	6201-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Country of origin	CZ
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	290%	370%		290%	1,19 A
@ D 265V 60Hz	290%			300%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000060084
P000060085



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

