

Model No. 6-Pole cage motor 5RN 71M 0,25kW D230V 50Hz IM3641-FT115

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	0,25	1/3	1,46	870	2,7	IE2	61,6	0,70	2,60	2,30	2,30
400	Y				0,84								
265	D	60	0,28	0,375	1,51	1070	2,5	IE2	59,5	0,70	2,80	2,30	2,30
460	Y				0,87								

Motor type	5RN71M06E23
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	71M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	0,25 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	37 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Rotor type	Cage motor
Bearing type	6202-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Phase resistance at 20°C	38,2040 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	230%	260%		230%	1,05 A
@ D 265V 60Hz	230%	278%		230%	0,98 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3641-FT115
Cooling method	IC411
Motor weight - approx.	08 kg
Gross weight - approx.	08 kg
Motor inertia	0,0010 kgm ²
Vibration level	according IEC60034-14

Direction of rotation	cw / ccw
-----------------------	----------

Schematic presentation of torque-speed curve



P000057252
P000057253



Driving efficiency and sustainability

