

Model No. 2-Pole cage motor 5RN 90L 2,2kW D230V 50Hz IM2081-FF165

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	2,2	3	7,62	2890	7,3	IE2	83,4	0,86	7,00	3,50	3,50
400	Y				4,4								
265	D	60	2,55	3,418	7,36	3480	7,0	IE2	85,5	0,87	7,00	3,50	3,50
460	Y				4,25								

Motor type	5RN90L02E26
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	90L
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	2,2 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	79 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM2081-FF165
Cooling method	IC411
Motor weight - approx.	17 kg
Gross weight - approx.	18 kg

Vibration level according IEC60034-14

Direction of rotation cw / ccw

Rotor type	Cage motor
Bearing type	6205-2Z/C3WT

Type of grease Unirex N3

Phase resistance at 20°C	2,2400 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	350%	699%	280%	350%	
@ D 265V 60Hz	350%	699%	300%	350%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000012353
P000013136



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

