

Model No. 4-Pole cage motor 5RN 90L 1,5kW D230V 50Hz IM2181-FT130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
230	D	50	1,5	2	5,89	1440	9,9	IE2	82,8	82,8		0,77			6,70	3,10	3,40
400	Y				3,4												
265	D	60	1,75	2 1/3	5,8	1740	9,6	IE2	84,0			0,77			6,70	3,10	3,40
460	Y				3,4												

Motor type	5RN90L04E26
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	90L
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM2181-FT130
Cooling method	IC411
Motor weight - approx.	17 kg
Gross weight - approx.	18 kg

Vibration level according IEC60034-14

Direction of rotation cw /ccw

Rotor type	Cage motor
Bearing type	6205-2Z/C3WT

Type of grease Unirex N3

Phase resistance at 20°C	3,4400 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	310%	670%	210%	340%	
@ D 265V 60Hz	310%	668%		340%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000012356
P000012976



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

