

Model No. 2-Pole cage motor 6RD 112M 4kW D400V 50Hz IM2101-FT130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	4	5 1/3	7,27	2903	13,2	IE3	88,1	0,90	8,40	2,10	3,50
690	Y				4,19								
460	D	60	4	5 1/3	6,4	3473	11,0	IE3	89,5	0,88	10,50	2,40	4,00

Motor type	6RD112M2E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	112M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	4 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb
Te time	0 sec

Rotor type	Cage motor
Bearing type	6306-2Z

Type of grease	Unirex N3
----------------	-----------


Country of origin	IT
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	210%	839%		350%	2,6 A
@ D 460V 60Hz	240%	1050%		400%	2,6 A

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

Degree of protection	IP55
Mounting type	IM2101-FT130
Cooling method	IC411
Motor weight - approx.	61 kg
Gross weight - approx.	63 kg
Motor inertia	0,0081 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C



P000057496
P000064305



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

