

**Model No.** 2-Pole cage motor 6RD 180M 22kW D400V 50Hz IM2001-FF300

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D             | 50        | 22        | 30        | 38,7     | 2963       | 70,9      | IE3         | 92,7                               | 0,88                            | 7,82                                   | 2,05                                   | 3,40                                   |
| 690      | Y             |           |           |           | 22,3     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 460      | D             | 60        | 22        | 30        | 34,5     | 3563       | 59,0      | IE3         | 91,7                               | 0,87                            | 8,05                                   | 2,10                                   |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RD180M2E3                   |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 180M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 22 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | ExII2G Ex db eb IIC T4 Gb    |
| Te time                       | 0 sec                        |

|              |            |
|--------------|------------|
| Rotor type   | Cage motor |
| Bearing type | 6310-2Z/C3 |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | IT |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 205%                              | 782%                           |                              | 340%                           | 15,6 A                    |
| @ D 460V 60Hz | 210%                              | 805%                           |                              |                                |                           |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM2001-FF300            |
| Cooling method         | IC411                   |
| Motor weight - approx. | 340 kg                  |
| Gross weight - approx. | 350 kg                  |
| Motor inertia          | 0,1265 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |
| Direction of rotation  | cw /ccw                 |
|                        | PTC 150°C               |

Schematic presentation of torque-speed curve



P000057517  
P000061982



Driving efficiency and sustainability

