

Model No. 4-Pole cage motor 6RD 200L 30kW D400V 50Hz IM3011-FF350

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	30	40	53,1	1482	193,3	IE3	93,6	0,85	8,14	2,20	3,10
690	Y				30,7								
460	D	60	34,5	46,25	54,4	1778	185,3	IE2	93,6	0,85	8,10	2,20	3,10
795	Y				31,4								

Motor type	6RD200LA4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	200L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	30 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb
Te time	0 sec

Rotor type	Cage motor
Bearing type	6312-2Z/C3

Type of grease	Unirex N3
----------------	-----------

Country of origin	CZ
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	220%	813%		310%	19,4 A
@ D 460V 60Hz	220%	808%		310%	21 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF350
Cooling method	IC411
Motor weight - approx.	420 kg
Gross weight - approx.	430 kg
Motor inertia	0,4379 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000057520
P000059339



Driving efficiency and sustainability

