

Model No. 4-Pole cage motor 6RD 315M 132kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	132	175	226	1489	846,6	IE3	95,6	0,86	7,44	2,11	3,10
690	Y				130								

Motor type	6RD315MB4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	132 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb

Rotor type	Cage motor
Bearing type	6316-2Z/C3

Type of grease	Unirex N3
----------------	-----------


Country of origin	IT
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	211%	743%		310%	74,4 A

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

Degree of protection	IP55
Mounting type	IM1001
Cooling method	IC411
Motor weight - approx.	1480 kg
Gross weight - approx.	1520 kg
Motor inertia	3,3145 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw



P000057543



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

