

Model No. 2-Pole cage motor 6RD 71A 0,37kW D230V 50Hz IM2001-FF130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	0,37	1/2	1,8	2872	1,2	IE2	69,5	0,74	4,74	2,50	2,70
400	Y				1,04								
265	D	60	0,43	0,576	1,61	3421	1,2	IE2	73,4 71,0 65,1	0,79 0,76 0,63	4,60	2,45	2,65
460	Y				0,93								

Motor type	6RD71A2E2
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	71A
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	0,37 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb
Te time	0 sec

Rotor type	Cage motor
Bearing type	6203-2Z

Type of grease	Unirex N3
----------------	-----------

Country of origin	IT
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	250%	473%		270%	0,935 A
@ D 265V 60Hz	245%	422%		265%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2001-FF130
Cooling method	IC411
Motor weight - approx.	20 kg
Gross weight - approx.	21 kg
Motor inertia	0,0004 kgm ²
Vibration level	according IEC60034-14

Direction of rotation	cw /ccw
-----------------------	---------

Schematic presentation of torque-speed curve



P000058760
P000059383



Driving efficiency and sustainability

