

Model No. 4-Pole cage motor 6RD 71B 0,37kW D400V 50Hz IM3001-FF130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	0,37	1/2	1,01	1385	2,6	IE2	72,7	0,73	3,88	2,40	2,76
690	Y				0,58								
460	D	60	0,42	0,563	1	1664	2,4	IE2	72,0	0,73	3,90	2,40	2,76

Motor type	6RD71B4E2
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	71B
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	0,37 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb
Te time	0 sec

Rotor type	Cage motor
Bearing type	6203-2Z

Type of grease	Unirex N3
----------------	-----------

Country of origin	IT
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	240%	386%		276%	0,81 A
@ D 460V 60Hz	240%	390%		276%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3001-FF130
Cooling method	IC411
Motor weight - approx.	kg
Gross weight - approx.	kg
Motor inertia	0,0009 kgm ²
Vibration level	according IEC60034-14

Direction of rotation	cw / ccw
-----------------------	----------

Schematic presentation of torque-speed curve



P000061137
P000066956



Driving efficiency and sustainability

