

Model No. 2-Pole cage motor 6RD 80M 1,1kW D230V 50Hz IM3601-FT100

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	1,1	1 1/2	4,01	2861	3,7	IE3	83,0	0,83	7,56	3,50	3,50
400	Y				2,31								
265	D	60	1,3	1,743	4,01	3433	3,6	IE2	83,0	0,83	7,50	3,50	3,50
460	Y				2,31								

Motor type	6RD80MB2E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	80M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,1 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	ExII2G Ex db eb IIC T4 Gb
Te time	0 sec

Degree of protection	IP55
Mounting type	IM3601-FT100
Cooling method	IC411
Motor weight - approx.	28 kg
Gross weight - approx.	29 kg
Motor inertia	0,0012 kgm ²
Vibration level	according IEC60034-14

Rotor type	Cage motor
Bearing type	6204-2Z
Type of grease	Unirex N3


Country of origin	IT
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	350%	755%		350%	2,17 A
@ D 265V 60Hz	350%	748%		350%	

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



Driving efficiency and sustainability

