

Model No. 4-Pole cage motor 6RN 100L 2,55kW D254V 60Hz IM1081

[illegible]

Motor type	6RN100L04E34	Degree of protection	IP55
Enclosure	Totally Enclosed Fan Cooling	Mounting type	IM1081
Frame Material	Cast iron	Cooling method	IC411
Frame size	100L	Motor weight - approx.	42 kg
Duty	S1	Gross weight - approx.	43 kg
Voltage	254 V	Motor inertia	0,0140 kgm²
Frequency	60 Hz		
Power output	2,55 kW	Vibration level	according IEC60034-14
		Noise level (pressure) acc 60034-9	62 dB(A)
Insulation class	F		
Ambient temperature	-20 till 40 °C		
Temperature rise	-		
Temperature rise surface		Direction of rotation	cw /ccw
Altitude above sea level	1000 mtr		
Hazardous area classification	Safe area		
Te time	0 sec		
Rotor type	Cage motor		
Bearing type	6306-2Z/C3WT		
Type of grease	Unirex N3		

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 254V 60Hz	182%	758%	134%	336%	

NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000041421

