

Model No. 2-Pole cage motor 6RN 112M 5,5kW D230V 50Hz IM3041-FF215

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 5,5       | 7 1/3     | 18,8     | 2935       | 17,9      | IE1         | 84,8 84,8 82,9                     | 0,86 0,79 0,68                  | 8,75                                   | 2,82                                   | 3,72                                   |
| 400      | Y             |           |           |           | 10,8     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 265      | D             | 60        | 6,3       | 8,445     | 18,2     | 3535       | 17,0      | IE1         | 87,1                               | 0,87                            | 9,81                                   | 3,29                                   | 3,86                                   |
| 460      | Y             |           |           |           | 10,5     |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN112M02E16                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 112M                         |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 5,5 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise exceeds class H    |
| Temperature rise winding      | 88 K                         |
| Temperature rise surface      | 30 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6306-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 230V 50Hz | 282%                              | 872%                           |                              | 372%                           | 9,36 A                    |
| @ D 265V 60Hz | 329%                              | 978%                           |                              | 386%                           | 8,11 A                    |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM3041-FF215            |
| Cooling method         | IC411                   |
| Motor weight - approx. | 48 kg                   |
| Gross weight - approx. | 49 kg                   |
| Motor inertia          | 0,0085 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |
| Direction of rotation  | cw / ccw                |

Schematic presentation of torque-speed curve



P000041409  
P000041410



Driving efficiency and sustainability

