

Model No. 2-Pole cage motor 6RN 112M 5,5kW D400V 50Hz IM3041-FF215

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	5,5	7 1/3	10,4	2950	17,8	IE3	89,2	90,5	90,0	0,86	0,81	0,70	9,44	2,50	3,70
690	Y				6												
460	D	60	6,3	8,445	10	3550	16,9	IE3	91,1	90,5	89,4	0,87	0,82	0,75	10,20	2,62	3,98

Motor type	6RN112M02E36
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	112M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	5,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	59 K
Temperature rise surface	23 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM3041-FF215
Cooling method	IC411
Motor weight - approx.	46 kg
Gross weight - approx.	47 kg

Vibration level according IEC60034-14

Direction of rotation cw / ccw

Rotor type	Cage motor
Bearing type	6306-2Z/C3WT

Type of grease Unirex N3

Phase resistance at 20°C	2,1928 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	250%	944%	200%	370%	4,4 A
@ D 460V 60Hz	262%	1020%		398%	3,74 A

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000034388
P000034545



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

