

Model No. 2-Pole cage motor 6RN 112M 5,5kW D400V 50Hz IM3641-FT165

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D             | 50        | 5,5       | 7 1/3     | 10,4     | 2950       | 17,8      | IE3         | 89,2 90,5 90,0                     | 0,86 0,81 0,70                  | 9,44                                   | 2,50                                   | 3,70                                   |
| 690      | Y             |           |           |           | 6        |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 460      | D             | 60        | 6,3       | 8,445     | 10       | 3550       | 16,9      | IE3         | 91,1 90,5 89,4                     | 0,87 0,82 0,75                  | 10,20                                  | 2,62                                   | 3,98                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN112M02E36                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 112M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 5,5 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 59 K                         |
| Temperature rise surface      | 23 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                        |              |
|------------------------|--------------|
| Degree of protection   | IP55         |
| Mounting type          | IM3641-FT165 |
| Cooling method         | IC411        |
| Motor weight - approx. | 46 kg        |
| Gross weight - approx. | 47 kg        |

Vibration level according IEC60034-14

Direction of rotation cw / ccw

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6306-2Z/C3WT |

Type of grease Unirex N3

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 2,1928 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 250%                              | 944%                           | 200%                         | 370%                           | 4,4 A                     |
| @ D 460V 60Hz | 262%                              | 1020%                          |                              | 398%                           | 3,74 A                    |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

Schematic presentation of torque-speed curve



P000034388  
P000034545



Driving efficiency and sustainability

