

Model No. 2-Pole cage motor 6RN 132M 15kW D400V 50Hz IM2081-FF265

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	15	20	27	2955	48,5	IE3	91,9	0,87	8,40	2,20	4,80
690	Y				15,7								
460	D	60	17,3	23,19	27,5	3565	46,3	IE3	91,7	0,86	11,10	3,00	4,80

Motor type	6RN132M02E37
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	15 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	34 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM2081-FF265
Cooling method	IC411
Motor weight - approx.	85 kg
Gross weight - approx.	88 kg
Motor inertia	0,0330 kgm ²
Vibration level	according IEC60034-14

Rotor type	Cage motor
Bearing type	6308-2Z/C3WT


Type of grease	Unirex N3
----------------	-----------

Country of origin	CZ
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	220%	837%		480%	13,7 A
@ D 460V 60Hz	300%	1109%		480%	

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000046959
P000061559



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

