

**Model No.** 2-Pole cage motor 6RN 132M 15kW D400V 50Hz IM3641-FT165

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D             | 50        | 15        | 20        | 27       | 2955       | 48,5      | IE3         | 91,9                               | 0,87                            | 8,40                                   | 2,20                                   | 4,80                                   |
| 690      | Y             |           |           |           | 15,7     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 460      | D             | 60        | 17,3      | 23,19     | 27,5     | 3565       | 46,3      | IE3         | 91,7                               | 0,86                            | 11,10                                  | 3,00                                   | 4,80                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN132M02E37                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 132M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 15 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      | 34 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6308-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [% nom] | Pull-up<br>Torque [% nom] | Breakdown<br>Torque [% nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|-----------------------------|---------------------------|-----------------------------|------------------------|
| @ D 400V 50Hz | 220%                              | 837%                        |                           | 480%                        | 13,7 A                 |
| @ D 460V 60Hz | 300%                              | 1109%                       |                           | 480%                        |                        |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM3641-FT165            |
| Cooling method         | IC411                   |
| Motor weight - approx. | 83 kg                   |
| Gross weight - approx. | 85 kg                   |
| Motor inertia          | 0,0330 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |

|                       |          |
|-----------------------|----------|
| Direction of rotation | cw / ccw |
|-----------------------|----------|

Schematic presentation of torque-speed curve



P000046959  
P000061559



Driving efficiency and sustainability

