

Model No. 6-Pole cage motor 6RN 132M 5,5kW D230V 50Hz IM3041-FF265

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
230	D	50	5,5	7 1/3	22,1	955	55,0	IE1	83,9	84,9	83,7	0,75	0,67	0,54	5,75	2,66	2,91
400	Y				12,7												
265	D	60	6,3	8,445	21,1	1155	52,1	IE1	86,2	87,1	86,2	0,76	0,69	0,57	6,24	2,67	3,04
460	Y				12,2												

Motor type	6RN132M06E13
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	5,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	84 K
Temperature rise surface	45 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM3041-FF265
Cooling method	IC411
Motor weight - approx.	68 kg
Gross weight - approx.	70 kg
Motor inertia	0,0270 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	63 dB(A)

Direction of rotation **cw / ccw**

Rotor type	Cage motor
Bearing type	6308-2Z/C3WT

Type of grease **Unirex N3**

Country of origin **CZ**

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	266%	574%	239%	291%	12,9 A
@ D 265V 60Hz	267%	625%	233%	304%	11,5 A

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000041413
P000041414



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

