

**Model No.** 4-Pole cage motor 6RN 132S 5,5kW D400V 50Hz IM1081

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D             | 50        | 5,5       | 7 1/3     | 10,5     | 1470       | 35,7      | IE4         | 91,9 92,5 92,3                     | 0,82 0,77 0,67                  | 8,25                                   | 2,64                                   | 3,58                                   |
| 690      | Y             |           |           |           | 6        |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 460      | D             | 60        | 6,3       | 8,445     | 10,3     | 1770       | 34,0      | IE4         | 92,4 92,9 92,6                     | 0,83 0,79 0,70                  | 8,36                                   | 2,56                                   | 3,54                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN132S04E40                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 132S                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 5,5 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 36 K                         |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM1081                  |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 75 kg                   |
| Gross weight - approx.             | 77 kg                   |
| Motor inertia                      | 0,0460 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 56 dB(A)                |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6308-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 1,5939 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [% nom] | Pull-up<br>Torque [% nom] | Breakdown<br>Torque [% nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|-----------------------------|---------------------------|-----------------------------|------------------------|
| @ D 400V 50Hz | 264%                              | 856%                        | 176%                      | 358%                        | 4,36 A                 |
| @ D 460V 60Hz | 256%                              | 866%                        | 134%                      | 354%                        | 4,03 A                 |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1


Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

Schematic presentation of torque-speed curve



P000040320  
P000040351



Driving efficiency and sustainability

