

**Model No.** 4-Pole cage motor 6RN 160L 22kW D440V 60Hz IM3041-FF300

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 440      | D             | 60        | 22        | 30        | 36,8     | 1769       | 118,8     | IE3         | 93,3                               | 0,84                            | 7,26                                   | 2,48                                   | 3,36                                   |
|          |               |           |           |           |          |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN160L04E36                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 160L                         |
| Duty                          | S1                           |
| Voltage                       | 440 V                        |
| Frequency                     | 60 Hz                        |
| Power output                  | 22 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 60 K                         |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM3041-FF300            |
| Cooling method         | IC411                   |
| Motor weight - approx. | 141 kg                  |
| Gross weight - approx. | 145 kg                  |
| Motor inertia          | 0,1010 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6309-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|


| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 440V 60Hz | 248%                              | 725%                           |                              | 336%                           | 15,7 A                    |
|               |                                   |                                |                              |                                |                           |

**NOTE**  
All performance values at rated voltage and frequency.  
All performance parameters are subjected to standard tolerance as per IEC 60034-1  
Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.



P000058551



Driving efficiency and sustainability

