

**Model No.** 8-Pole cage motor 6RN 160L 7,5kW D230V 50Hz IM3041-FF300

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 7,5       | 10        | 33       | 728        | 98,4      | IE3         |                                    |                                 | 3,80                                   | 1,60                                   | 3,80                                   |
| 400      | Y             |           |           |           | 19,1     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 265      | D             | 60        | 8,6       | 11,53     | 28,6     | 880        | 93,3      | IE2         | 88,5                               | 0,74                            | 6,10                                   | 2,30                                   | 2,70                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN160L08E34                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 160L                         |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 7,5 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6309-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [%<br>nom] | Pull-up<br>Torque [%<br>nom] | Breakdown<br>Torque [%<br>nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|------------------------|
| @ D 230V 50Hz | 160%                              | 378%                           |                              | 380%                           |                        |
| @ D 265V 60Hz | 230%                              | 608%                           |                              | 270%                           |                        |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3041-FF300            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 110 kg                  |
| Gross weight - approx.             | 113 kg                  |
| Motor inertia                      | 0,1160 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 65 dB(A)                |

|                       |         |
|-----------------------|---------|
| Direction of rotation | cw /ccw |
|-----------------------|---------|

Schematic presentation of torque-speed curve



P000041381  
P000041382



Driving efficiency and sustainability

