

Model No. 2-Pole cage motor 6RN 160M 15kW D400V 50Hz IM1081

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |      |  | PF at __load |  |  | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|------|--|--------------|--|--|----------------------------------------|----------------------------------------|----------------------------------------|
| FL       | 3/4FL         | 1/2FL     | FL        | 3/4FL     | 1/2FL    |            |           |             |                  |      |  |              |  |  |                                        |                                        |                                        |
| 400      | D             | 50        | 15        | 20        | 27,7     | 2952       | 48,5      | IE2         | 90,5             | 90,3 |  | 0,88         |  |  | 7,60                                   | 2,40                                   | 3,40                                   |
| 690      | Y             |           |           |           | 16       |            |           |             |                  |      |  |              |  |  |                                        |                                        |                                        |
| 460      | D             | 60        | 17,3      | 23,19     | 27,4     | 3553       | 46,5      | IE2         | 90,7             |      |  | 0,88         |  |  | 8,00                                   | 2,24                                   | 3,19                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN160M02E23                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 160M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 15 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. H             |
| Temperature rise winding      | 81 K                         |
| Temperature rise surface      | 18 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM1081                  |
| Cooling method         | IC411                   |
| Motor weight - approx. | 101 kg                  |
| Gross weight - approx. | 104 kg                  |
| Motor inertia          | 0,0530 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6309-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,4519 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque<br>[% nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 240%                              | 758%                           |                              | 340%                           | 10,5 A                    |
| @ D 460V 60Hz | 224%                              | 795%                           |                              | 319%                           | 9,11 A                    |

#### NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.



P000011880  
P000011881



Driving efficiency and sustainability

