

Model No. 2-Pole cage motor 6RN 180M 22kW D400V 50Hz IM2021-FF300

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	22	30	39,7	2940	71,5	IE2	92,2 92,4 91,7	0,87 0,82 0,73	7,85	2,73	3,66
690	Y				23,1								
460	D	60	24,5	32,84	38,1	3540	66,1	IE2	92,3 92,3 91,2	0,87 0,83 0,75	8,33	2,80	3,80

Motor type	6RN180M02E22
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	180M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	22 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	75 K
Temperature rise surface	13 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM2021-FF300
Cooling method	IC411
Motor weight - approx.	145 kg
Gross weight - approx.	149 kg
Motor inertia	0,0690 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	68 dB(A)

Rotor type	Cage motor
Bearing type	6310-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Phase resistance at 20°C	0,3496 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	273%	785%	210%	366%	14,6 A
@ D 460V 60Hz	280%	834%	210%	380%	13,2 A

NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000014421
P000014422



Driving efficiency and sustainability

