

Model No. 2-Pole cage motor 6RN 200L 30kW D400V 50Hz IM3021-FF350

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	30	40	54,3	2955	97,0	IE2	93,7 93,9 93,2	0,86 0,82 0,74	7,17	2,46	3,36
690	Y				31,3								
460	D	60	33,5	44,91	52,2	3555	90,0	IE2	93,5 93,3 92,0	0,87 0,83 0,75	7,30	2,54	3,40

Motor type	6RN200L02E24
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	200L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	30 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	61 K
Temperature rise surface	23 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM3021-FF350
Cooling method	IC411
Motor weight - approx.	200 kg
Gross weight - approx.	206 kg
Motor inertia	0,1300 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	71 dB(A)

Rotor type	Cage motor
Bearing type	6312-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Phase resistance at 20°C	0,1918 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	246%	716%	200%	336%	18,8 A
@ D 460V 60Hz	254%	727%	200%	340%	17,3 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000014437
P000014445



Driving efficiency and sustainability

