

**Model No.** 4-Pole cage motor 6RN 200L 37kW D230V 50Hz IM3021-FF350

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 37        | 49,6      | 120      | 1475       | 239,6     | IE3         | 94,4 94,9 94,7                     | 0,81 0,76 0,66                  | 8,14                                   | 3,03                                   | 3,53                                   |
| 400      | Y             |           |           |           | 69,6     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 265      | D             | 60        | 42,5      | 56,97     | 118      | 1775       | 228,7     | IE3         | 95,0 95,4 95,2                     | 0,83 0,78 0,68                  | 8,54                                   | 2,86                                   | 3,44                                   |
| 460      | Y             |           |           |           | 68       |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN200L04E36                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 200L                         |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 37 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 63 K                         |
| Temperature rise surface      | 36 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3021-FF350            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 260 kg                  |
| Gross weight - approx.             | 270 kg                  |
| Motor inertia                      | 0,2750 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 65 dB(A)                |

Direction of rotation cw / ccw

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6312-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,0446 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 230V 50Hz | 303%                              | 817%                           | 279%                         | 353%                           | 50,8 A                    |
| @ D 265V 60Hz | 286%                              | 855%                           | 277%                         | 344%                           | 46,3 A                    |

### NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |



P000041147  
P000041148



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

