

Model No. 6-Pole cage motor 6RN 200L 22kW D440V 60Hz IM3021-FF350

[illegible]

Motor type	6RN200L06E35	Degree of protection	IP55
Enclosure	Totally Enclosed Fan Cooling	Mounting type	IM3021-FF350
Frame Material	Cast iron	Cooling method	IC411
Frame size	200L	Motor weight - approx.	242 kg
Duty	S1	Gross weight - approx.	249 kg
Voltage	440 V	Motor inertia	0,3200 kgm²
Frequency	60 Hz		
Power output	22 kW	Vibration level	according IEC60034-14
		Noise level (pressure) acc 60034-9	61 dB(A)
Insulation class	F		
Ambient temperature	-20 till 40 °C		
Temperature rise	temp.rise acc. B		
Temperature rise winding	50 K		
Temperature rise surface	31 K	Direction of rotation	cw /ccw
Altitude above sea level	1000 mtr		
Hazardous area classification	Safe area		
Te time	0 sec		
Rotor type	Cage motor		
Bearing type	6312-2Z/C3WT		
Type of grease	Unirex N3		

	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
Voltage/Freq					
@ D 440V 60Hz	230%	623%	170%	240%	16,7 A

NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000046216

