

Model No. 2-Pole cage motor 6RN 225M 55kW D400V 50Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	55	75	97	2960	177,4	IE2	93,7	94,1	93,7	0,88	0,85	0,78	7,53	2,45	3,33
690	Y				56												
460	D	60	62	83,11	94	3560	166,3	IE2	93,0	93,1	92,5	0,89	0,87	0,81	7,00	2,50	3,30

Motor type	6RN225M02E26
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	225M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	55 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	69 K
Temperature rise surface	33 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	300 kg
Gross weight - approx.	310 kg
Motor inertia	0,2600 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	71,2 dB(A)

Rotor type	Cage motor
Bearing type	6313/C3
Lubrication method	22gr/4000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0785 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	245%	748%	231%	333%	28,6 A
@ D 460V 60Hz	250%	700%		330%	28 A

NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000015098
P000015132



Driving efficiency and sustainability

