

Model No. 2-Pole cage motor 6RN 225M 52kW D440V 60Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
440	D	60	52	69,71	80,5	3553	139,8	IE3	94,2	0,90	6,55	2,10	2,75

Motor type	6RN225M02E32
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	225M
Duty	S1
Voltage	440 V
Frequency	60 Hz
Power output	52 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	64 K
Temperature rise surface	32 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	330 kg
Gross weight - approx.	340 kg
Motor inertia	0,2600 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	72 dB(A)

Rotor type	Cage motor
Bearing type	6313/C3
Lubrication method	22gr/2950hrs
Type of grease	Unirex N3

Direction of rotation cw / ccw

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 440V 60Hz	210%	654%	195%	275%	18,8 A

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000018196



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

