

Model No. 6-Pole cage motor 6RN 225M 37kW D400V 50Hz IM2021-FF400

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	37	49,6	70	985	358,7	IE3	93,3	93,9	93,7	0,82	0,79	0,70	7,60	3,00	3,30
690	Y				40,5												
460	D	60	44,5	59,65	69	1180	360,1	IE2	93,3	94,0	94,0	0,85	0,83	0,76	7,30	2,24	2,59

Motor type	6RN225M06E36
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	225M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	37 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. H
Temperature rise winding	80 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Rotor type	Cage motor
Bearing type	6313/C3
Lubrication method	22gr/13400hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,2056 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	300%	760%		330%	
@ D 460V 60Hz	224%	746%	244%	259%	21,5 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2021-FF400
Cooling method	IC411
Motor weight - approx.	390 kg
Gross weight - approx.	400 kg
Motor inertia	0,8400 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	0 dB(A)

Direction of rotation cw / ccw

Schematic presentation of torque-speed curve



P000017373
P000017374



Driving efficiency and sustainability

