

**Model No.** 2-Pole cage motor 6RN 250M 62kW D440V 60Hz IM2021-FF500

| U<br>(V) | Δ/Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|-------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 440      | D           | 60        | 62        | 83,11     | 96       | 3572       | 165,8     | IE3         | 94,1                               | 0,90                            | 6,46                                   | 1,99                                   | 2,66                                   |
|          |             |           |           |           |          |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN250M02E32                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 250M                         |
| Duty                          | S1                           |
| Voltage                       | 440 V                        |
| Frequency                     | 60 Hz                        |
| Power output                  | 62 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. F             |
| Temperature rise winding      | 65 K                         |
| Temperature rise surface      | 30 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|                    |              |
|--------------------|--------------|
| Rotor type         | Cage motor   |
| Bearing type       | 6315/C3      |
| Lubrication method | 25gr/1800hrs |
| Type of grease     | Unirex N3    |

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 440V 60Hz | 199%                              | 645%                           | 164%                         | 266%                           | 23,8 A                    |
|               |                                   |                                |                              |                                |                           |

**NOTE**  
All performance values at rated voltage and frequency.  
All performance parameters are subjected to standard tolerance as per IEC 60034-1  
Voltage, Frequency are as per IEC60034-1  
Technical data are subject to change. There may be discrepancies between calculated and name plate values.


|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM2021-FF500            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 420 kg                  |
| Gross weight - approx.             | 430 kg                  |
| Motor inertia                      | 0,4600 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 77 dB(A)                |

|                       |         |
|-----------------------|---------|
| Direction of rotation | cw /ccw |
|-----------------------|---------|

Schematic presentation of torque-speed curve



P000018902



Driving efficiency and sustainability

