

Model No. 2-Pole cage motor 6RN 250 75kW D400V 50Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	75	100	129	2980	240,4	IE4	95,6	0,88	10,30	3,00	3,90
690	Y				74,5								
460	D	60	86	115,3	128	3581	229,3	IE4	95,8	0,88	10,30	3,00	3,90

Motor type	6RN250M02E46
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	250
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	75 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Rotor type	Cage motor
Bearing type	6315/C3
Lubrication method	25gr/4000hrs
Type of grease	Unirex N3

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	300%			390%	
@ D 460V 60Hz	300%			390%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	470 kg
Gross weight - approx.	480 kg

Vibration level according IEC60034-14

Direction of rotation cw /ccw

Schematic presentation of torque-speed curve



P000061447
P000063092



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

