

Model No. 2-Pole cage motor 6RN 280M 104kW D440V 60Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
440	D	60	104	139,4	160	3570	278,2	IE2	94,4	0,91	6,81	2,12	2,71

Motor type	6RN280M02E32
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	280M
Duty	S1
Voltage	440 V
Frequency	60 Hz
Power output	104 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. H
Temperature rise winding	77 K
Temperature rise surface	35 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	590 kg
Gross weight - approx.	610 kg
Motor inertia	0,9400 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	73 dB(A)

Rotor type	Cage motor
Bearing type	6315/C3
Lubrication method	25gr/1800hrs
Type of grease	Unirex N3


Direction of rotation cw / ccw

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 440V 60Hz	212%	675%	170%	271%	32,3 A

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000018293



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

