

Model No. 6-Pole cage motor 6RN 280M 55kW D400V 50Hz IM2021-FF500

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |       |       | PF at __ load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
|          |               |           |           |           |          |            |           |             | FL               | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL |                                        |                                        |                                        |
| 400      | D             | 50        | 55        | 75        | 99,8     | 988        | 531,6     | IE3         | 93,9             | 94,4  | 94,2  | 0,85          | 0,81  | 0,72  | 7,55                                   | 2,94                                   | 2,86                                   |
| 690      | Y             |           |           |           | 57,7     |            |           |             |                  |       |       |               |       |       |                                        |                                        |                                        |
| 460      | D             | 60        | 55        | 75        | 87,4     | 1190       | 441,4     | IE3         | 94,5             | 94,6  | 94,0  | 0,84          | 0,79  | 0,70  | 8,53                                   | 3,33                                   | 3,19                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN280M06E32                 |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 280M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 55 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 50 K                         |
| Temperature rise surface      | 31 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|                    |              |
|--------------------|--------------|
| Rotor type         | Cage motor   |
| Bearing type       | 6317/C3      |
| Lubrication method | 30gr/8000hrs |
| Type of grease     | Unirex N3    |

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,1180 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 294%                              | 754%                           | 210%                         | 286%                           | 32,5 A                    |
| @ D 460V 60Hz | 333%                              | 852%                           | 240%                         | 319%                           | 30,7 A                    |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM2021-FF500            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 570 kg                  |
| Gross weight - approx.             | 590 kg                  |
| Motor inertia                      | 1,6000 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 58 dB(A)                |

|                       |          |
|-----------------------|----------|
| Direction of rotation | cw / ccw |
|-----------------------|----------|

Schematic presentation of torque-speed curve



P000014509  
P000014510



Driving efficiency and sustainability

