

Model No. 6-Pole cage motor 6RN 280S 45kW D400V 50Hz IM3021-FF500

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	45	60,32	83,5	985	436,3	IE2	92,3	93,0	92,9	0,84	0,81	0,72	6,49	2,60	2,55
690	Y				48,3												
460	D	60	45	60,32	73	1185	362,7	IE2	93,5	93,7	93,1	0,83	0,79	0,69	8,04	2,90	2,86

Motor type	6RN280S06E20
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	280S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	45 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	63 K
Temperature rise surface	31 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM3021-FF500
Cooling method	IC411
Motor weight - approx.	460 kg
Gross weight - approx.	470 kg
Motor inertia	1,1000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	61 dB(A)

Rotor type	Cage motor
Bearing type	6317/C3
Lubrication method	30gr/8000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,1859 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	260%	647%	235%	255%	29,9 A
@ D 460V 60Hz	290%	802%	200%	286%	28,2 A

NOTE

All performance values at rated voltage and frequency.


All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.



P000014579
 P000014580



Driving efficiency and sustainability

