

Model No. 2-Pole cage motor 6RN 315L 200kW D400V 50Hz IM3011-FF600

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	200	268,1	330	2982	640,5	IE2	95,5	95,8	95,4	0,92	0,92	0,88	7,88	2,50	2,98
690	Y				191												
460	D	60	224	300,3	320	3580	597,5	IE2	95,2	95,2	94,6	0,92	0,92	0,89	7,84	2,72	2,85

Motor type	6RN315L02E25
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	200 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	69 K
Temperature rise surface	29 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6316/C3
Lubrication method	30gr/3000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0154 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	250%	781%	193%	298%	59,4 A
@ D 460V 60Hz	272%	784%	186%	285%	56,5 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30


This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF600
Cooling method	IC411
Motor weight - approx.	1130 kg
Gross weight - approx.	1160 kg
Motor inertia	2,2000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	78 dB(A)

Direction of rotation cw /ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000014591
P000014592



Driving efficiency and sustainability

