

Model No. 6-Pole cage motor 6RN 315L 110kW D400V 50Hz IM2001-FF600

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	110	150	196	988	1063,3	IE1	94,2	94,5	94,1	0,85	0,82	0,74	7,27	2,54	2,75
690	Y				114												
460	D	60	132	175	200	1186	1062,9	IE1	94,1			0,87			6,70	2,40	2,60

Motor type	6RN315L06E14
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	110 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	82 K
Temperature rise surface	53 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0542 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	254%	724%	226%	275%	72 A
@ D 460V 60Hz	240%	670%	210%	260%	69,4 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2001-FF600
Cooling method	IC411
Motor weight - approx.	920 kg
Gross weight - approx.	950 kg
Motor inertia	3,2000 kgm ²
Vibration level	according IEC60034-14

Direction of rotation cw /ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000040302

P000018151



Driving efficiency and sustainability

