

Model No. 6-Pole cage motor 6RN 315L 160kW D440V 60Hz IM1011

U (V)	Δ/Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
440	D	60	160	214,5	259	1191	1283,0	IE2	95,7	0,85	9,00	2,96	3,41

Motor type	6RN315L06E36
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	440 V
Frequency	60 Hz
Power output	160 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	54 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 440V 60Hz	296%	899%	179%	341%	100 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1011
Cooling method	IC411
Motor weight - approx.	1160 kg
Gross weight - approx.	1190 kg
Motor inertia	4,6000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	66 dB(A)

Direction of rotation cw /ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000060191



Driving efficiency and sustainability

