

Model No. 8-Pole cage motor 6RN 315L 110kW D400V 50Hz IM1011

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	110	150	205	740	1419,6	IE3	93,7	94,2	94,1	0,82	0,78	0,68	6,70	2,70	2,90
690	Y				118												
460	D	60	132	175	210	888	1419,6	IE3	94,5	95,0	95,0	0,83	0,80	0,71	5,90	2,20	2,65

Motor type	6RN315L08E35
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	110 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	270%	668%		290%	
@ D 460V 60Hz	220%	585%		265%	74,1 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1011
Cooling method	IC411
Motor weight - approx.	1000 kg
Gross weight - approx.	1030 kg
Motor inertia	3,9000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	68,4 dB(A)
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000040087

P000040088



Driving efficiency and sustainability

