

**Model No.** 2-Pole cage motor 6RN 315M 132kW D400V 50Hz IM3011-FF600

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |       |       | PF at __ load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
|          |               |           |           |           |          |            |           |             | FL               | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL |                                        |                                        |                                        |
| 400      | D             | 50        | 132       | 175       | 220      | 2988       | 421,9     | IE4         | 96,2             | 96,2  | 95,6  | 0,90          | 0,90  | 0,86  | 10,70                                  | 2,90                                   | 3,90                                   |
| 690      | Y             |           |           |           | 128      |            |           |             |                  |       |       |               |       |       |                                        |                                        |                                        |
| 460      | D             | 60        | 148       | 198,4     | 215      | 3588       | 393,9     | IE4         | 95,8             | 95,8  | 95,2  | 0,90          | 0,89  | 0,85  | 10,70                                  | 2,90                                   | 3,90                                   |

|                |                              |
|----------------|------------------------------|
| Motor type     | 6RN315M02E42                 |
| Enclosure      | Totally Enclosed Fan Cooling |
| Frame Material | Cast iron                    |
| Frame size     | 315M                         |
| Duty           | S1                           |
| Voltage        | 400 V                        |
| Frequency      | 50 Hz                        |
| Power output   | 132 kW                       |

|                               |                |
|-------------------------------|----------------|
| Insulation class              | F              |
| Ambient temperature           | -20 till 40 °C |
| Temperature rise              | -              |
| Temperature rise surface      |                |
| Altitude above sea level      | 1000 mtr       |
| Hazardous area classification | Safe area      |

|                    |              |
|--------------------|--------------|
| Rotor type         | Cage motor   |
| Bearing type       | 6316/C3      |
| Lubrication method | 30gr/3000hrs |
| Type of grease     | Unirex N3    |

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [%<br>nom] | Pull-up<br>Torque [%<br>nom] | Breakdown<br>Torque [%<br>nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|------------------------|
| @ D 400V 50Hz | 290%                              | 1068%                          |                              | 390%                           |                        |
| @ D 460V 60Hz | 290%                              |                                |                              | 390%                           |                        |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3011-FF600            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 980 kg                  |
| Gross weight - approx.             | 1010 kg                 |
| Motor inertia                      | 1,9000 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 82 dB(A)                |

|                       |           |
|-----------------------|-----------|
| Direction of rotation | cw /ccw   |
|                       | PTC 150°C |

Schematic presentation of torque-speed curve



P000041981  
P000049225



Driving efficiency and sustainability

